



# CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC23001412228

Valid from: Nov.27,2023

Valid until:Nov.07,2027

**NAME AND REGISTERED ADDRESS OF THE APPLICANT** Guangdong Aote Semiconductor Co.,Ltd  
3rd Floor, Building 1, No. 596 Zhoushi Road, Jiuwei Community, Hangcheng Street, Bao'an District, Shenzhen

**NAME AND REGISTERED ADDRESS OF THE MANUFACTURER** Guangdong Aote Semiconductor Co.,Ltd  
3rd Floor, Building 1, No. 596 Zhoushi Road, Jiuwei Community, Hangcheng Street, Bao'an District, Shenzhen

**NAME AND LOCATION OF THE FACTORY** FUJIAN LIGHTNING OPTOELECTRONIC CO.,LTD  
No.4 Yingbin Road, Hengshan Village , Photoelectric Industrial Park, Hutou Town, Anxi County, Fujian Province, China

**PRODUCT NAME, MODEL AND SPECIFICATION** Optocoupler  
See appendix(Altitude up to 5000m)

**THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS** GB 4943.1-2022

**TYPE OF CERTIFICATION SCHEMES** type test+follow up factory inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-471543-2022.  
The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

The certificate information is available through the QR code below or CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn)



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE





# CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO. : CQC23001412228

page 1 of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

型号	内部爬电距离规格 ( mm )	外部爬电距离规格 ( mm )	内部穿透距离 ( 绝缘厚度 ) 规格 ( mm )
AT618XN(Y)(Z)-FGV、AT810XN(Y)(Z)-GV、 AT814XN(Y)(Z)-GV、AT8145XN(Y)(Z)-GV、 AT815XN(Y)(Z)-GV、AT816XN(Y)(Z)-FGV、 AT816LXN(Y)(Z)-FGV、 AT817XN(Y)(Z)-FGV、AT818XN(Y)(Z)-GV、 AT819XN(Y)(Z)-GV、AT851XN(Y)(Z)-GV、 AT852XN(Y)(Z)-GV、AT3010-4L(Y)(Z)-GV、 AT3011-4L(Y)(Z)-GV、AT3012-4L(Y)(Z)-GV、 AT3021-4L(Y)(Z)-GV、AT3022-4L(Y)(Z)-GV、 AT3023-4L(Y)(Z)-GV、AT3051-4L(Y)(Z)-GV、 AT3052-4L(Y)(Z)-GV、AT3053-4L(Y)(Z)-GV、 AT3071-4L(Y)(Z)-GV、AT3072-4L(Y)(Z)-GV、 AT3073-4L(Y)(Z)-GV、AT3031-4L(Y)(Z)-GV、 AT3032-4L(Y)(Z)-GV、AT3033-4L(Y)(Z)-GV、 AT3041-4L(Y)(Z)-GV、AT3042-4L(Y)(Z)-GV、 AT3043-4L(Y)(Z)-GV、AT3061-4L(Y)(Z)-GV、 AT3062-4L(Y)(Z)-GV、AT3063-4L(Y)(Z)-GV、 AT3081-4L(Y)(Z)-GV、AT3082-4L(Y)(Z)-GV、 AT3083-4L(Y)(Z)-GV、 ATR21NX-4L(Y)(Z)-GV、 ATR41NX-4L(Y)(Z)-GV、 AT521XN(Y)(Z)-FGV、AT785XN(Y)(Z)-FGV、 AT2501XN(Y)(Z)-FGV、 AT2561XN(Y)(Z)-FGV、AT824XN(Y)(Z)-GV、 AT825XN(Y)(Z)-GV、AT826XN(Y)(Z)-GV、 AT827XN(Y)(Z)-GV (在产品外包装的标签上体现完整型号，上面	N/A	≥7.6	≥0.4



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO. : CQC23001412228

page2of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

<p>所示型号中的变量解释如下： 其中 X, N 代表档次或分类, X 可以是 A-Z 或空白, N 可以是 1-9 或空白, Y 代表脚型, 可以是 M, S, SL, SLM, 空白(表示 DIP); Z 代表编带类型, 可以是 T1, T2, T3, T4 或是空白(DIP 类无需编带); F 代表导线架材料类型, F 代表铁材, 铜材则为空白; G 代表环保材料类型, 非环保材料则为空白; V 代表 VDE 认证, 无则空白, 其中, “-” 用于区分前字段和后字段, 无任何意义, 因电脑打印系统硬件限制, “-” 可能会被省略。)</p>			
---	--	--	--



CHINA QUALITY CERTIFICATION CENTRE