



CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC23001412230

Valid from: Nov.27,2023

Valid until:Aug.27,2028

NAME AND REGISTERED ADDRESS OF THE APPLICANT Guangdong Aote Semiconductor Co.,Ltd
3rd Floor, Building 1, No. 596 Zhoushi Road, Jiuwei Community, Hangcheng Street, Bao'an District, Shenzhen

NAME AND REGISTERED ADDRESS OF THE MANUFACTURER Guangdong Aote Semiconductor Co.,Ltd
3rd Floor, Building 1, No. 596 Zhoushi Road, Jiuwei Community, Hangcheng Street, Bao'an District, Shenzhen

NAME AND LOCATION OF THE FACTORY FUJIAN LIGHTNING OPTOELECTRONIC CO.,LTD
No.4 Yingbin Road, Hengshan Village , Photoelectric Industrial Park, Hutou Town, Anxi County, Fujian Province, China

PRODUCT NAME, MODEL AND SPECIFICATION Optocoupler
See appendix(Altitude up to 5000m)

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS GB 4943.1-2022

TYPE OF CERTIFICATION SCHEMES type test+follow up factory inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-471543-2022.
The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE





CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO. : CQC23001412230

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

ATL501(P)(Z)-GV(H)、ATL501(W)(Z)-GV(H)、ATL601(P)(Z)-GV(H)、ATL601(W)(Z)-GV(H)、ATL611(P)(Z)-GV(H)、
ATL611(W)(Z)-GV(H)、ATL701(P)(Z)-GV(H)、ATL701(W)(Z)-GV(H)、ATL50L(P)(Z)-GV(H)、ATL50L(W)(Z)-GV(H)、
ATL60L(P)(Z)-GV(H)、ATL60L(W)(Z)-GV(H)、ATL61L(P)(Z)-GV(H)、ATL61L(W)(Z)-GV(H)、ATL70L(P)(Z)-GV(H)、
ATL70L(W)(Z)-GV(H)、ATL21L(P)(Z)-GV(H)、ATL21L(W)(Z)-GV(H)、ATL302(P)(Z)-GV(H)、ATL302(W)(Z)-GV(H)、
ATL314(P)(Z)-GV(H)、ATL314(W)(Z)-GV(H)、ATL340(P)(Z)-GV(H)、ATL340(W)(Z)-GV(H)、ATL341(P)(Z)-GV(H)、
ATL341(W)(Z)-GV(H)、ATL343(P)(Z)-GV(H)、ATL343(W)(Z)-GV(H)、ATL345(W)(Z)-GV(H)、ATL346(P)(Z)-GV(H)、
ATL346(W)(Z)-GV(H)、ATL345(P)(Z)-GV(H)、ATL347(P)(Z)-GV(H)、ATL347(W)(Z)-GV(H)、ATL349(P)(Z)-GV(H)、
ATL349(W)(Z)-GV(H)、ATL454(P)(Z)-GV(H)、ATL454(W)(Z)-GV(H)、ATL456(P)(Z)-GV(H)、ATL456(W)(Z)-GV(H)、
ATL480(P)(Z)-GV(H)、ATL480(W)(Z)-GV(H)、ATL481(P)(Z)-GV(H)、ATL481(W)(Z)-GV(H)、ATL483(P)(Z)-GV(H)、
ATL483(W)(Z)-GV(H)、ATL484(P)(Z)-GV(H)、ATL484(W)(Z)-GV(H)

(在产品外包装的标签上体现完整型号，上面所示型号中的变量解释如下：其中(P)或(W)是脚型，固定的不变，此款产品有两种脚型；Z代表编带类型，可以是T1，T2，T3，T4；G代表环保材料类型，非环保材料则为空白；V代表VDE认证，无则空白；H代表125高温产品，常温则空白；其中，“-”用于区分前字段和后字段，无任何意义，因电脑打印系统硬件限制，“-”可能会被省略。)

规格：加强绝缘，有效值工作电压：240V，峰值工作电压：420V，外部爬电距离规格(mm)：≥6.0，内部穿透距离(绝缘厚度)规格(mm)：≥0.4，通过125℃的热循环试验



CHINA QUALITY CERTIFICATION CENTRE